



FLOW



Vortex Mass Flowmeter

Tek-Vor 1300C

1 FEATURES

- It has a lower measuring limit, better stability, and accuracy
- It has a unique dual sensor design
- Special signal processing method provides better anti-vibration
- It can calculate density and mass flow rate without a mass flow computer
- An Optional Bluetooth function is available, it can read flow rate on smart phone
- It has a self-diagnostic function

3 APPLICATIONS

- Food and Beverages
- Water, wastewater treatment plants
- Process industry
- Petrochemical
- Pharmaceutical industries

CONTACT US

796 Tek Drive, Crystal Lake, IL 60014 USA

+1 847 857 6076
+1 847 655 7428

Email: tektrol@tek-trol.com

www.tek-trol.com

2 SPECIFICATION

Nominal diameter	1" to 12" (0.04 ft to 1 ft)		
Measurement range in Ft/sec (m/s)	Size	1" (0.08 ft)	1 ½" to 12" (0.12 to 1 ft)
	Fluid Flow Rate	Steam	13.12 to 229.6 ft/sec (4 to 70 m/s)
		Gas	13.12 ft/sec to 196.85 ft/sec (4 to 60 m/s)
		Liquid	0.98 to 22.96 ft/sec (0.3 to 7 m/s)
Accuracy	±1% of Reading For Multivariable Version: Temperature ±1 °F, Pressure: 0.75% FS		
Repeatability	0.3% of Reading		
Output	4 to 20 mA and Pulse 4 to 20 mA, Pulse and HART 4 to 20 mA, Pulse and RS485 modbus		
Maximum process pressure limit	150# ANSI Flange, 300# ANSI Flange		
Process temperature range	-40 °F to 302 °F (-40 °C to 150 °C) or -40 °F to 482 °F (-40 °C to 250 °C) or -40 °F to 662 °F (-40 °C to 350 °C)		
Ambient humidity	5 to 100% RH		
Process connection	Wafer, 150# ANSI Flange, 300# ANSI Flange		
Electrical connection	½" NPT		
Material	304 SS, 316 SS		